

# DRE Vista Flex

## LED Examination Light

### Offers a variety of mounting and illumination options

The DRE Vista Flex is a versatile LED examination light with maximum positioning capabilities, making it ideal for Dermatology, Plastic Surgery, ENT, OB/GYN, Ophthalmology, Outpatient Surgery, Family Practice and more. The dual-segmented gooseneck arm and universal mounting clip allow clinicians to position the light precisely where they need it.

Complete with adjustable spot, user-friendly control panel and an extended length power cable.

#### FEATURES

- Bright LED examination light ideal for a wide range of medical specialties.
- Cost-saving, energy-efficient LED bulb produces up to 50,000 hours of illumination.
- Available in a variety of mounting options including a mobile stand, wall mount or table mount.
- Universal clip allows clinicians to easily attach the light to any table or procedure chair.
- Flexible gooseneck light arm features two segments for maximum positioning capabilities.
- Light produces 70,000 Lux at an eight inch working distance.
- Bright white color temperature accurately illuminates tissue.
- Control panel features intuitive controls and two handles for easily maneuvering the lighting unit.
- Streamlined design for easy cleaning and sterilization.
- Power cable measures nearly 10 feet.



1393-2021-03-18

#### SPECIFICATIONS



**LED:** 1 White 3W LED Bulb

**Lifetime:** 50,000 hours

**Color Temperature:**  
5,000 - 5,500K

**Adjustable Spot Diameter**  
(working distance 7.87"):  
0.59 - 1.97"

**Illuminance**  
(working distance 7.87"):  
70,000 lux



**Gooseneck Length:** 39.37"

**Stand Height:** 27.56"

**Base Diameter:** 19.69"

**Package Measurement:**  
33.86 x 24.02 x 6.3"



**Gross Weight:** 13.22lb (6kg)

**Net Weight:** 7.72lb (3.5kg)



**Voltage:** DC 5V

**Power:** 5W

**Power Cable:**  
5.5x2.1mm

**Adapter:**  
Input: AC100-240V ~ 50Hz/Hz  
Output: DC 5V

Distance	7.87 in	11.81 in	15.75 in	19.66 in	23.62 in	31.50 in	39.37 in
Lux Max	70,000	30,000	15,000	9,500	6,500	3,500	2,300
Circle of light (max)	1.77 in	2.56 in	3.54 in	4.33 in	5.31 in	7.48 in	8.66 in
Circle of light (min)	0.39 in	0.71 in	0.79 in	0.98 in	1.06 in	1.38 in	1.69 in

